



**NOTES:**

- UNLESS OTHERWISE APPROVED, BICYCLE PARKING RACKS SHALL BE "INVERTED U TYPE" CYCLE-SAFE U/2 BLACK PLASTISOL COATED BY MANUFACTURER OR APPROVED EQUIVALENT. OTHER RACKS MAY BE ALLOWED BUT MUST MEET THE FOLLOWING FUNCTIONAL REQUIREMENTS:
  - SUPPORT THE FRAME OF A BICYCLE IN TWO PLACES AND PREVENT THE BICYCLE FROM TIPPING OVER.
  - ALLOW THE FRAME AND ONE WHEEL TO BE LOCKED TO THE RACK WHEN BOTH WHEELS ARE LEFT ON THE BIKE.
  - ALLOW THE FRAME AND BOTH WHEELS TO BE LOCKED TO THE RACK IF THE FRONT WHEEL IS REMOVED.
  - ALLOW THE USE OF EITHER A CABLE OR U-SHAPED LOCK.
  - BE SECURELY ANCHORED BY SURFACE MOUNT.
  - BE USABLE BY BIKES WITH NO KICKSTAND.
  - BE USABLE BY BIKES WITH WATER BOTTLE CAGES.
  - BE USABLE BY A WIDE VARIETY OF SIZES AND TYPES OF BICYCLES.
  - BE COATED BY MANUFACTURER
- INSTALL PER MANUFACTURER'S RECOMENDATION.

**STANDARD DETAIL  
BICYCLE PARKING RACK**



SCALE: AS SHOWN	DESIGNED	DRAWN CAW	APPROVED BY	STANDARD SPECIFICATIONS	REVISIONS	
					DATE	INITIAL
10/09/2020	CHECKED		DATE APPROVED		03/31/2023	JTB

DETAIL NO.  
**R-950**

PAGE  
**1 OF 1**