



**NOTE:**  
ALL COMPONENTS TO BE THERMOPLASTIC POWDERED COATED BLACK.

**PIPE SCHEDULE**  
(ALL DIMENSIONS I.D.)

BOTTOM RAIL	CORNER/END POST	LINE POST
1.25"	2.5"	2"

**NOTES:**

1. ALL FENCING MATERIALS SHALL COMPLY WITH THE WSDOT/APWA STANDARD SPECIFICATIONS SECTION 9-16 CLASS 1 MATERIAL. INSTALLATIONS PER MANUFACTURER'S RECOMMENDATIONS.
2. SHOP DRAWINGS OF RAILING SHALL BE SUBMITTED FOR APPROVAL SHOWING COMPLETE DIMENSIONS AND DETAILS OF FABRICATION AND INCLUDING AN ERECTION DIAGRAM. MATERIALS BEING USED SHALL BE SPECIFIED IN THE SHOP DRAWINGS.
3. ALL STEEL PARTS SHALL BE GIVEN A BLACK ULTRAVIOLET-INSENSITIVE THERMOPLASTIC POWDER COATING AT LEAST 3 MILS THICK AND SHALL HAVE A UNIFORM FINISH.
4. CUTTING SHALL BE DONE BY SAWING OR MILLING AND ALL CUTS SHALL BE TRUE AND SMOOTH. FLAME CUTTING WILL NOT BE PERMITTED.
5. ALL MATERIALS SHALL BE ADEQUATELY WRAPPED TO ENSURE SURFACE PROTECTION DURING HANDLING AND TRANSPORTATION TO THE JOB SITE.
6. ANY WELDING OF STEEL SHALL BE IN ACCORDANCE WITH THE LATEST AASHTO STANDARD SPECIFICATIONS FOR STRUCTURAL SUPPORTS FOR HIGHWAY SIGNS, LUMINARIES AND TRAFFIC SIGNALS.
7. PANEL HEIGHT: 36 INCHES FOR ALL PEDESTRIAN USES  
42 INCHES FOR BIKE PATHS

**STANDARD DETAIL**  
**CHAIN LINK SIDEWALK**  
**SAFETY RAIL**



SCALE: AS SHOWN	DESIGNED	DRAWN	CAW	APPROVED BY	STANDARD SPECIFICATIONS	REVISIONS	
						DATE	INITIAL
						10/21/2020	JTB
						03/07/2024	

DETAIL NO.  
**R-450C**

PAGE  
**3 OF 3**